Forest Products Journal Index...1974

All the articles in the 1974 *Journal* are listed both by subject and by author. The Subject Index is organized according to the FPRS Division and Technical Committee structure.

The Author Index lists senior author entries which give complete information for the article, and co-author entries which refer back to the senior author.

Reprints of all the articles listed are available at a cost of 20¢ per printed page with a maximum $1.50 charge per reprint. Bulk rates are also available. The reprint number and cost per single reprint are listed for each entry. A check or money order must accompany each order.

FPRS Subject Index . . . Vol. 24, 1974

PRODUCTS DIVISION

Softwood Lumber

Ammoniacal Zinc Oxide Treatment as an Inhibitor of Fungi in Pine Lumber, J. K. Shields, R. L. Desai, and M. R. Clarke, 2:54 (No. 5133–$.80)

Analysis of the Effect of the Lumber Recovery Factor (LRF) on Sawmill Costs, T. K. McEwan, 3:17 (No. 5103–$.60)

CCA Retention and Disproportioning in White Spruce, M. Y. Cech, F. Pfaff, and D. R. Huffman, 7:26 (No. 5185–$1.40)

Edge-Glued Dimension Lumber from Low-Grade Southern Pine, R. H. McAlister, 7:17 (No. 5178–$1.20)

Effect of Size on Tensile Strength of Clear Douglas-fir and Hem-fir, R. H. Kunesh and J. W. Johnson, 8:32 (No. 5197–$1.00)

Evaluation of Models for Predicting Tensile Strength of 2- by 4-Inch Lumber, C. C. Gerhards, and R. L. Ethington, 12:46 (No. 5247–$1.50)

Longitudinal Shrinkage of Western Redcedar, Western Hemlock, and True Fir, L. D. Espenas, 10:46 (TN-281–$.60)

Lumber Production: Analyzing Costs, Sales, and Supply Relationships, J. Host, 11:49 (No. 5234–$1.20)

Noise Levels in Softwood Lumber Mills, W. A. Dost, 8:25 (No. TN-272–$.60)

Potassium Fertilizer Effects on the Static Bending Properties of Red Pine Wood, R. L. Gray and G. H. Kyanka, 9:92 (No. 5152–$1.00)

Predicting Product Recovery in Southern Pine Using Dendrometry and STX, J. C. Space, 9:85 (No. 5198–$.60)

Serrated Kiln Sticks and Top Load Substantially Reduce Warp in Southern Pine Studs Dried at 240°F, P. Koch, 11:30 (No. 5256–$1.00)

Strength Characteristics of Two-Ply Vertically Laminated Beams of Southern Pine, R. H. McAlister, 8:39 (No. 5214–$1.00)

Tensile Strength of Douglas-Fir Laminated-Veneer Lumber, J. C. Bohlen, 1:54 (No. 5111–$1.00)

Time to Dry 2-, 3-, and 4-Inch S4S Southern Pine at 240°F, as Related to Board Width, P. Koch, 3:35 (No. 5067–$1.00)

Trials of Prototype Roll-Feed, High Temperature Dryer for 8/4 Southern Pine, P. Koch, 5:24 (No. 5175–$1.00)

Weight-Scaling Tree-Length Timber for Veneer Logs, Saw Logs, and Pulpwood, C. A. Fasick, G. L. Tyre, and F. M. Riley, Jr., 6:17 (No. 5188–$.80)

Hardwood Lumber

Aspen Lumber and Dimension Stock Recovery in Relation to Sawing Pattern, Y. Robichaud, F. J. Petro, and M. C. S. Kingsley, 3:26 (No. 5126–$1.00)

Bleaching of Mineral-Stained Maple, N. Levitin, 8:28 (No. 5171–$1.00)

Comparison of Factors Affecting Power for Abrasive and Knife Planing of Hardwoods, H. A. Stewart, 3:31 (No. 5139–$.80)

Eastern Hardwood Resources: Trends and Prospects, H. S. Sternitzke, 3:13 (No. 5183–$.80)

Effect of Kiln Air Velocity, at Various Moisture Content Levels, on Drying Rate of 4/4 Yellow-Poplar Sapwood, H-P. Steinhagen, 4:45 (No. 4943–$.60)

Freezing and Thawing Times for Black Walnut, G. A. Cooper and S. H. Barham, 6:54 (No. 5170–$.60)

Hardwood Resources on Southern Pine Sites, P. A. Murphy and H. A. Knight, 7:13 (No. 5238–$.80)

High-Temperature Kiln-Drying of Northern Aspen 2- by 4-Inch Light-Framing Lumber, J. F. G. Mackay, 10:32 (No. 5237–$.80)

Log and Sawmill Simulation Through Computer Graphics, S. M. Pnevmaticos, P. E. Dress, and F. R. Stocker, 3:53 (No. 5119–$.60)

Logs vs. Bolts: Effect of Length on Dimension Stock Yields, S. M. Pnevmaticos and I. B. Flann, 6:49 (No. 5050–$.60)

Maximum Initial Moisture Content for Kiln-Drying 4/4 Hardwoods at High Temperatures, E. M. Wengert, 8:54 (No. 5221–$.60)

Present and Prospective Hardwood Utilization in the South, J. F. Christopher, 10:13 (No. 5252–$.60)

Weight-Scaling Tree-Length Timber for Veneer Logs, Saw Logs, and Pulpwood, C. A. Fasick, G. L. Tyre, and F. M. Riley, Jr., 6:17 (No. 5188–$.80)

Treated Wood Products

Ammoniacal Zinc Oxide Treatment as an Inhibitor of Fungi in Pine Lumber, J. K. Shields, R. L. Desai, and M. R. Clarke, 2:54 (No. 5133–$.80)

Biodeterioration of Particleboard, E. R. Toole and H. M. Barnes, 10:55 (No. 5254–$.60)

CCA Retention and Disproportioning in White Spruce, M. Y. Cech, F. Pfaff, and D. R. Huffman, 7:26 (No. 5185–$1.40)

Estimating Preservative Treatability of Wood From its Air-Flow Properties, P. A. Cooper, G. Bramhall, and N. A. Ross, 9:99 (No. 5200–$1.00)

New Fire-Retardant Treatment for Western Redcedar Shingles, F. W. King and S. C. Juneja, 2:18 (No. 5025–$1.20)

Organisms Causing Discoloration and Deterioration of Asphalt Shingles, T. L. Amburgey, 6:52 (No. 5149–$.60)

Permeability of Spruce Ponded in Newfoundland, H. H. Unligil and J. Krzyzewski, 12:33 (No. 5280–$1.00)

Uptake by Grape Plants of Preservatives From Pressure-Treated Posts Not Detected, M. P. Levi, D. Huisingh, and W. B. Nesbitt, 9:97 (No. 5208–$.40)

Versatile Fire Retardants from Amino Resins, S. C. Juneja and L. R. Richardson, 5:19 (No. 5094–$1.00)

Construction Plywood

Attapulgite Clay, a Filler and Exterior Plywood Adhesive, M. D. Strickler, and E. W. Sawyer, Jr., 11:17 (No. 5239–$1.20)

Comparisons of Air and Steam as Veneer Drying Media, W. W. Laity, G. H. Atherton, and J. R. Welty, 6:21 (No. 5030–$1.50)

Effect of Prescribed Defects on Tensile Properties of Douglas-Fir Plywood Strips, W. M. McGowan, 5:39 (No. 5150–$1.20)

Effect of Temperature, Time, and Drying Medium on the Strength and Gluability of Douglas-fir and Southern Pine Veneer, C. J. Kozlik, 2:46 (No. 5027–$1.50)

Evaluation of Asian Plywood Glue Extenders Based on Personal Plant-site Observations in 1973, J. E. Robertson, 11:35 (No. 5228–$1.40)

New Approach to Quality Control in the Manufacture of Exterior Softwood Plywood, M. N. Carroll, 4:24 (No. 5104–$1.40)

Steam-Injection Knife Improves Veneer Quality, D. C. Walser, 9:70 (No. 5222–$1.50)

Study of Dryout Resistance of Phenolic Copolymer Resins for Pine Plywood Glues – Part I, J. T. Rice and C. M. Chen, 3:20 (No. 5125–$1.40)

Decorative Veneers & Plywood

Evaluation of Asian Plywood Glue Extenders Based on Personal Plant-site Observations in 1973, J. E. Robertson, 11:35 (No. 5228–$1.40)

One-Step Method of Making Veneer Polymer Composite Overlaid Plywood by Gamma Radiation, L. Paszner, T. Kaneko, H. T. Cho, and M. M. Micko, 10:39 (No. 5179–$1.40)

Press-Drying Green, Flatsliced Walnut Veneer to Reduce Buckling and End Waviness, J. F. Lutz, H. Habermann, and H. R. Panzer, 5:29 (No. 5165–$1.20)

Particleboard & Molded Products

Apparatus to Facilitate Comparison of Abrasiveness of Wood Composition Panel Products, R. R. Stevens, 8:37 (No. TN-269–$.60)

Biodeterioration of Particleboard, E. R. Toole and H. M. Barnes, 10:55 (No. 5254–$.60)

Cross-Grain Cutting With Segmented Helical Cutters Produces Good Surfaces and Flakes, H. A. Stewart and W. F. Lehmann, 9:104 (No. 5077–$.60)

Determination of Elastic Parameters of Full Size Wood Composite Boards, T. E. McLain and J. Bodig, 4:48 (No. 5158–$1.50)

Effects of Species and Panel Densities on Properties of Exotic Hardwood Particleboard, B. E. Vital, W. F. Lehmann, and S. R. Boone, 12:37 (No. 5291–$1.50)

Efficiency of Resin-Wood Particle Blending, R. L. Christensen and P. Robitschek, 7:22 (No. 5196–$1.20)

Face Milling Can be Improved for Surfacing and Flaking, H. A. Stewart, 2:58 (No. 5140–$.40)

Future Outlook for Oregon's Particleboard Industry, W. W. Johnson and R. O. McMahon, 1:13 (No. 5137–$.60)

Impact Behavior of Particleboard as Related to Some Other Physical Properties, A. Johnson and J. G. Haygreen, 11:22 (No. 5245–$1.20)

Improving the Properties of Commercial Phenolic-Bonded, Structural-Type Particleboards by Oil Tempering, H. Hall and R. O. Gertjejansen, 3:40 (No. 5109–$.60)

Improving the Surface Quality of Particleboard by High-Temperature Pressing, K. C. Shen, 10:36 (No. 5206–$.80)

Modified Powdered Spent Sulfite Liquor as Binder for Exterior Waferboard, K. C. Shen, 2:38 (No. 5093–$1.40)

Needleboards–an Exploratory Study, E. T. Howard, 5:50 (TN-265–$.40)

New Torsion Test for Particleboard, P. Gaudert, 2:35 (TN-258–$.60)

Normal Resin Distribution in Particleboard Manufacture, T. F. Duncan, 6:36 (No. 5080–$1.50)

Prediction of Elastic Constants of Particleboard, M. O. Hunt and S. K. Suddarth, 5:52 (No. 5191–$1.20)

Properties of Structural Particleboards, W. F. Lehmann, 1:19 (No. 5070–$1.40)

Properties of Structural Particleboards from Douglas-Fir Forest Residues, W. F. Lehmann and R. L. Geimer, 10:17 (No. 5242–$1.50)

Slash Pine Rootwood in Flakeboard, E. T. Howard, 6:29 (No. 5167–$1.50)

Splitting of Wood-Base Building Boards Due to Edge Screwing, E. I. E. Didriksson, J. O. Nyren, and E. L. Back, 7:35 (No. 5186–$1.00)

Utilization of Ponderosa Pine Bark and Its Extract in Particleboard, A. B. Anderson, K-T. Wu and A. Wong, 8:48 (No. 5217–$1.20)

Utilization of White Fir Bark in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 1:51 (No. 5010–$.80)

Utilization of White Fir Bark and Its Extract in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 7:40 (No. 5164–$1.20)

Visual Method for Measuring Formaldehyde Release from Resin-Bonded Boards, J. M. Harkin, J. R. Obst, and W. F. Lehmann, 1:27 (No. 5110–$.80)

Hardboard & Insulation Board

Determination of Elastic Parameters of Full Size Wood Composite Boards, T. E. McLain and J. Bodig, 4:48 (No. 5158–$1.50)

Effects of Equilibrium Moisture Content Changes on Hardboard Properties, J. D. McNatt, 2:29 (No. 5087–$1.40)

Influence of Fiber Alignment on Stiffness and Dimensional Stability of High-Density Dry-Formed Hardboard, P. E. Steinmetz and C. W. Polley, 5:45 (No. 5160–$1.00)

Splitting of Wood-Base Building Boards Due to Edge Screwing, E. I. E. Didriksson, J. O. Nyren, and E. L. Back, 7:35 (No. 5186–$1.00)

Three Tests on Nailhead Performance in Wood-Base Panels, P. Chow, 11:41 (TN-278–$.80)

Furniture, Dimension & Turned Stock

Aspen Lumber and Dimension Stock Recovery in Relation to Sawing Pattern, Y. Robichaud, F. J. Petro, and M.C.S. Kingsley, 3:26 (No. 5126–$1.00)

Logs vs. Bolts: Effect of Length on Dimension Stock Yields, S.M. Pnevmaticos and I. B. Flann, 6:49 (No. 5050–$.60)

Pulp & Paper

Full-Tree and Complete-Tree Utilization for Pulp and Paper, J. L. Keays, 11:13 (No. 5277–$.80)

Seedling Characteristics and Kraft Pulping Properties of Young Douglas-Fir, W. J. Bublitz and S. N. Chia, 3:48 (No. 5135–$1.00)

Weight-Scaling Tree-Length Timber for Veneer Logs, Saw Logs, and Pulpwood, C. A. Fasick, G. L. Tyre, and F. M. Riley, Jr., 6:17 (No. 5188–$.80)

Laminated Wood, Components, & Engineered Structures

Description of a Laminated Oak Beam L. J. Nemeth, 12:27 (No. 4903–$1.20)

Edge-Glued Dimension Lumber From Low-Grade Southern Pine, R. H. McAlister, 7:17 (No. 5178–$1.20)

Gusset Plates from Plywood and Hardboard Scrap, D. H. Percival, S. K. Suddarth, and Q. B. Comus, 3:43 (TN-268–$.40)

Residual Strength of Fire-Damaged Laminated Beams, S. P. Fox, 1:48 (TN-255–$.60)

Shear Strength of Wood Beams, F. J. Keenan, 9:63 (No. 5144–$1.50)

Strength and Stiffness of Roof Diaphragms with Different Percentages of the Decking Edge Glued, J. W. Johnson, 4:36 (TN-264–$.60)

Strength Characteristics of Two-Ply Vertically Laminated Beams of Southern Pine, R. H. McAlister, 8:39 (No. 5214–$1.00)

Tensile Strength of Douglas-Fir Laminated-Veneer Lumber, J. C. Bohlen, 1:54 (No. 5111–$1.00)

Timber Structures Reinforced With Light Gage Steel, G. E. Coleman and H. T. Hurst, 7:45 (No. 4934–$1.80)

Residential & Commercial Buildings

Comparison of Mechanical Properties for Non-Load-Bearing Panels in Walls, E. L. Back, E. I. E. Didriksson, and K. G. Norberg, 10:48 (No. 5207–$1.40)

Forest Products and the National Housing Goals, L. C. Irland, 2:12 (No. 5148–$1.20)

Gusset Plates from Plywood and Hardboard Scrap, D. H. Percival, S. K. Suddarth, and Q. B. Comus, 3:43 (TN-268–$.40)

High-Temperature Kiln-Drying of Northern Aspen 2- by 4-Inch Light-Framing Lumber, J. F. G. Mackay, 10:32 (No. 5237–$.80)

Marketability of Aspen Studs, R. D. Thompson, 12:23 (No. 5265–$1.00)

Methods of Nailing and Adhesive Rheology Affect the Strength of Nailed-Glued Construction Joints, H. F. Zornig and C. B. Vick, 12:17 (No. 5266–$1.20)

New Fire-Retardant Treatment for Western Redcedar Shingles, F. W. King and S. C. Juneja, 2:18 (No. 5025–$1.20)

Organisms Causing Discoloration and Deterioration of Asphalt Shingles, T. L. Amburgey, 6:52 (No. 5149–$.60)

Properties of Structural Particleboards, W. F. Lehmann, 1:19 (No. 5070–$1.40)

Properties of Structural Particleboards from Douglas-Fir Forest Residues, W. F. Lehmann and R. L. Geimer, 10:17 (No. 5242–$1.50)

Splitting of Wood-Base Building Boards Due to Edge Screwing, E. I. E. Didriksson, J. O. Nyren, and E. L. Back, 7:35 (No. 5186–$1.00)

Strength and Stiffness of Roof Diaphragms With Different Percentages of the Decking Edge Glued, J. W. Johnson, 4:36 (TN-264–$.60)

Pallets & Containers

Hardened-Steel Versus Stiff-Stock Nails in Warehouse Pallets, E. G. Stern, 11:55 (TN-277–$1.00)

Tropical Woods

Effects of Species and Panel Densities on Properties of Exotic Hardwood Particleboard, B. R. Vital, W. F. Lehmann, and R. S. Boone, 12:37 (No. 5291–$1.50)

Evaluation of Some Tropical Woods Imported Into the United States from South America, R. C. Gilmore and A. C. Barefoot, 2:24 (No. 5118–$1.00)

Kiln-Drying Selected Colombian Woods, J. M. McMillen and R. S. Boone, 4:31 (No. 5147–$1.20)

Survival and Feeding of Subterranean Termites on Tropical Woods, R. H. Beal, F. L. Carter, and C. R. Southwell, 8:44 (No. 5210–$1.00)

Bark & Residues

Bark Properties of Eight Western Softwoods, D. L. Cassens, 4:40 (No. 5073–$1.00)

Complete-Tree Concept: 1964-1974, H. E. Young, 12:13 (No. 5269–$.80)

Effect of Harvesting to Various Merchantable Limits on Loblolly Pine Logging Residue, A. Clark III and M. A. Taras, 6:45 (No. 5195–$.80)

Effect of Nitrogen and Composting on Decomposition of Barks from Four Hardwood Species, S. M. Still, M. A. Dirr, and J. B. Gartner, 7:54 (No. 5194–$.60)

Full-Tree and Complete-Tree Utilization for Pulp and Paper, J. L. Keays, 11:13 (No. 5277–$.80)

Gusset Plates from Plywood and Hardboard Scrap, D. H. Percival, S. K. Suddarth, and Q. B. Comus, 3:43 (TN-268–$.40)

Gross Heat of Combustion of Five Hardwood Species at Differing Moisture Contents, W. K. Murphey and B. E. Cutter, 2:44 (TN-253–$.40)

Investigation of the Chemically Reactive Constituents of Atmospheric Emissions From Hogged-Fuel-Fired Boilers in Oregon, D. C. Junge and K. T. Kwan, 10:25 (No. 5232–$1.00)

Logging Residues in Florida, Georgia, and South Carolina, R. L. Welch, 10:30 (No. 5235–$.60)

Needleboards–an Exploratory Study, E. T. Howard, 5:50 (TN-265–$.40)

Preliminary Economic Analysis of Whole-Tree Chipping and Bark Removal, F. E. Biltonen, J. R. Erickson, and J. A. Mattson, 3:45 (No. 5132–$.60)

Properties of Structural Particleboards from Douglas-Fir Forest Residues, W. F. Lehmann and R. L. Geimer, 10:17 (No. 5242–$1.50)

Reinforcing Plastics with Douglas-Fir Bark Fiber, D. J. Miller, J. D. Wellons, R. L. Krahmer, and P. H. Short, 8:18 (No. 5205–$1.20)

Removal of Emulsified Oil by Sorption on Southern Pine Bark, W. G. Glasser and F. S. Lin, 9:87 (No. 5215–$1.00)

Slash Pine Rootwood in Flakeboard, E. T. Howard, 6:29 (No. 5167–$1.50)

Use of Bark to Remove Heavy Metal Ions from Waste Solutions, J. M. Randall, V. Garrett, R. L. Berman, and A. C. Waiss, Jr., 9:80 (No. 5199–$1.00)

Utilization of Ponderosa Pine Bark and Its Extract in Particleboard, A. B. Anderson, K-T. Wu and A. Wong, 8:48 (No. 5217–$1.20)

Utilization of White Fir Bark in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 1:51 (No. 5010–$.80)

Utilization of White Fir Bark and Its Extract in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 7:40 (No. 5164–$1.20)

MANAGEMENT DIVISION

Production Management

Analysis of the Effect of the Lumber Recovery Factor (LRF) on Sawmill Costs, T. K. McEwan, 3:17 (No. 5103–$.60)

Weight-Scaling Tree-Length Timber for Veneer Logs, Saw Logs and Pulpwood, C. A. Fasick, G. L. Tyre, and F. M. Riley, Jr., 6:17 (No. 5188–$.80)

Log and Sawmill Simulation Through Computer Graphics, S. M. Pnevmaticos, P. E. Dress, and F. R. Stocker, 3:53 (No. 5119–$.60)

Logs vs. Bolts: Effect of Length on Dimension Stock Yields, S. M. Pnevmaticos and I. B. Flann, 6:49 (No. 5050–$.60)

Marketing

Forest Products and the National Housing Goals, L. C. Irland, 2:12 (No. 5148–$1.20)

Future Outlook for Oregon's Particleboard Industry, W. W. Johnson and R. O. McMahon, 1:13 (No. 5137–$.60)

Lumber Production: Analyzing Costs, Sales, and Supply Relationships, J. Host, 11:49 (No. 5234–$1.20)

Marketability of Aspen Studs, R. D. Thompson, 12:23 (No. 5265–$1.00)

Present and Prospective Hardwood Utilization in the South, J. F. Christopher, 10:13 (No. 5252–$.60)

Use of the Semantic Differential in Developing Forest Products Marketing Strategies, J. Dickson, 6:12 (No. 5136–$.40)

Economics & Financial Management

An Economist's View of the Pine-Site Hardwood Problem, W. C. Anderson, 4:14 (No. 5211–$.60)

Analysis of the Effect of the Lumber Recovery Factor (LRF) on Sawmill Costs, T. K. McEwan, 3:17 (No. 5103–$.60)

Forest Products and the National Housing Goals, L. C. Irland, 2:12 (No. 5148–$1.20)

Future Outlook for Oregon's Particleboard Industry, W. W. Johnson and R. O. McMahon, 1:13 (No. 5137–$.60)

Futures Markets: an Annotated Bibliography, L. C. Irland, 7:12 (No. TN-276–$.20)

Preliminary Economic Analysis of Whole-Tree Chipping and Bark Removal, F. E. Biltonen, J. R. Erickson, and J. A. Mattson, 3:45 (No. 5132–$.60)

Present and Prospective Hardwood Utilization in the South, J. F. Christopher, 10:13 (No. 5252–$.60)

Trends in Forest Land Values, A. Pleasonton, 1:16 (No. 5072–$.60)

Research Management

Cooperative Research Planning, A. E. Wylie, 9:55 (No. 5295–$.60)

Deciding on Priority Projects, H. M. Babcock, 9:52 (No. 5302–$.60)

Developments and Progress in Research Management, K. T. Adair, 4:11 (No. 5193–$.60)

Dilemma in Academic Research, G. G. Marra, 9:58 (No. 5293–$.80)

Response of a Public Research Laboratory to Changing Needs, H. O. Fleischer, 9:49 (No. 5305–$.60)

Strategic Planning of Research and Development at Weyerhaeuser, A. S. Gregory, 9:37 (No. 5292–$1.40)

Transfer of Science and Technology in Successful Innovation, L. A. Cox, 9:44 (No. 5294–$1.00)

Quality Control

New Approach to Quality Control in the Manufacture of Exterior Softwood Plywood, M. N. Carroll, 4:24 (No. 5104–$1.40)

PROCESSES DIVISION

Timber Production

An Economist's View of the Pine-Site Hardwood Problem, W. C. Anderson, 4:14 (No. 5211–$.60)

Eastern Hardwood Resources: Trends and Prospects, H. S. Sternitzke, 3:13 (No. 5183–$.80)

Effect of Harvesting to Various Merchantable Limits on Loblolly Pine Logging Residue, A. Clark III and M. A. Taras, 6:45 (No. 5195–$.80)

Hardwood Resources on Southern Pine Sites, P. A. Murphy and H. A. Knight, 7:13 (No. 5238–$.80)

Potassium Fertilization Effects on the Static Bending Properties of Red Pine Wood, R. L. Gray and G. H. Kyanka, 9:92 (No. 5152–$1.00)

Predicting Product Recovery in Southern Pine Using Dendrometry and STX, J. C. Space, 9:85 (No. 5198–$.60)

Trends in Forest Land Values, A. Pleasonton, 1:16 (No. 5072–$.60)

Drying & Storage

Comparisons of Air and Steam as Veneer Drying Media, W. W. Laity, G. H. Atherton, and J. R. Welty, 6:21 (No. 5030–$1.50)

Drying Tree Disks Simply and Without Defects, H. Kubler, 7:33 (No. 5042–$.60)

Effect of Kiln Air Velocity, at Various Moisture Content Levels, on Drying Rate of 4/4 Yellow-Poplar Sapwood, H-P. Steinhagen, 4:45 (No. 4943–$.60)

Effect of Temperature, Time, and Drying Medium on the Strength and Gluability of Douglas-fir and Southern Pine Veneer, C. J. Kozlik, 2:46 (No. 5027–$1.50)

Freezing and Thawing times for Black Walnut, G. A. Cooper and S. H. Barham, 6:54 (No. 5170–$.60)

High-Temperature Kiln-Drying of Northern Aspen 2- by 4-Inch Light-Framing Lumber, J. F. G. Mackay, 10:32 (No. 5237–$.80)

Improved Resistance Moisture Measurement Techniques: Pulsed Current Meter and Wood Element Sensors, R. F. Couture and J. L. Hill, 4:17 (No. 5123–$1.40)

Kiln-Drying Selected Colombian Woods, J. M. McMillen, and R. S. Boone, 4:31 (No. 5147–$1.20)

Longitudinal Shrinkage of Western Redcedar, Western Hemlock, and True Fir, L. D. Espenas, 10:46 (TN-281–$.60)

Maximum Initial Moisture Content for Kiln-Drying 4/4 Hardwoods at High Temperatures, E. M. Wengert, 8:54 (No. 5221–$.60)

"Pinned" Sticker to Reduce Crook in Kiln-Drying Lumber, E. M. Wengert and R. C. Baltes, 8:23 (No. TN-275–$.40)

Press-Drying Green, Flatsliced Walnut, Veneer to Reduce Buckling and End Waviness, J. F. Lutz, H. Habermann, and H. R. Panzer, 5:29 (No. 5165–$1.20)

Serrated Kiln Sticks and Top Load Substantially Reduce Warp in Southern Pine Studs Dried at 240°F, P. Koch, 11:30 (No. 5256–$1.00)

Time to Dry 2-, 3-, and 4-Inch S4S Southern Pine at 240°F, as Related to Board Width, P. Koch, 3:35 (No. 5067–$1.00)

Trials of Prototype Roll-Feed, High Temperature Dryer for 8/4 Southern Pine, P. Koch, 5:24 (No. 5175–$1.00)

Gluing

Attapulgite Clay, a Filler and Exterior Plywood Adhesive, M. D. Strickler, and E. W. Sawyer, Jr., 11:17 (No. 5239–$1.20)

Edge-Glued Dimension Lumber From Low-Grade Southern Pine, R. H. McAlister, 7:17 (No. 5178–$1.20)

Effect of Temperature, Time, and Drying Medium on the Strength and Gluability of Douglas-Fir and Southern Pine Veneer, C. J. Kozlik, 2:46 (No. 5027–$1.50)

Efficiency of Resin-Wood Particle Blending, R. L. Christensen and P. Robitschek, 7:22 (No. 5196–$1.20)

Evaluation of Asian Plywood Glue Extenders Based on Personal Plant-site Observations in 1973, J. E. Robertson, 11:35 (No. 5228–$1.40)

Evaluation of Some Tropical Woods Imported into the United States from South America, R. C. Gilmore and A. C. Barefoot, 2:24 (No. 5118–$1.00)

Measuring Durability of Adhesive Resins on Paper Substrates, R. E. Kreibich and A. G. Andersen, 1:36 (No. 5031–$.80)

Methods of Nailing and Adhesive Rheology Affect the Strength of Nailed-Glued Construction Joints, H. F. Zornig and C. B. Vick, 12:17 (No. 5266–$1.20)

Modified Powdered Spent Sulfite Liquor as Binder for Exterior Waferboard, K. C. Shen, 2:38 (No. 5093–$1.40)

Normal Resin Distribution in Particleboard Manufacture, T. F. Duncan, 6:36 (No. 5080–$1.50)

Resistance to Cyclic Exposure at Extreme Low Temperature of Urea Resin Bonds, S. Chow and P. R. Steiner, 5:35 (No. 5157–$.80)

Softening Temperature, Ash Content, and Bond Quality of Polyvinyl-Acetate-Emulsion Adhesives, E. G. Bergin and S. Chow, 11:45 (No. 5231–$1.00)

Strength and Stiffness of Roof Diaphragms With Different Percentages of the Decking Edge Glued, J. W. Johnson 4:36 (TN-264–$.60)

Study of Dryout Resistance of Phenolic Copolymer Resins for Pine Plywood Glues – Part I, J. T. Rice and C. M. Chen, 3:20 (No. 5125–$1.40)

Utilization of Ponderosa Pine Bark and Its Extract in Particleboard, A. B. Anderson, K-T. Wu and A. Wong, 8:48 (No. 5217–$1.20)

Utilization of White Fir Bark in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 1:51 (No. 5010–$.80)

Utilization of White Fir Bark and Its Extract in Particleboard, A. B. Anderson, A. Wong, and K-T. Wu, 7:40 (No. 5164–$1.20)

Mechanical Fastening

Hardened-Steel Versus Stiff-Stock Nails in Warehouse Pallets, E. G. Stern, 11:55 (TN-277–$1.00)

Three Tests on Nailhead Performance in Wood-Base Panels, P. Chow, 11:41 (TN-278–$.80)

Splitting of Wood-Base Building Boards Due to Edge Screwing, E. I. E. Didriksson, J. O. Nyren, and E. L. Back, 7:35 (No. 5186–$1.00)

Milling & Machining

Analysis of the Effect of the Lumber Recovery Factor (LFR) on Sawmill Costs, T. K. McEwan, 3:17 (No. 5103–$.60)

Apparatus to Facilitate Comparison of Abrasiveness of Wood Composition Panel Products, R. R. Stevens, 8:37 (No. TN-269–$.60)

Aspen Lumber and Dimension Stock Recovery in Relation to Sawing Pattern, Y. Robichaud, F. J. Petro, and M. C. S. Kingsley, 3:26 (No. 5126–$1.00)

Comparison of Factors Affecting Power for Abrasive and Knife Planing of Hardwoods, H. A. Stewart, 3:31 (No. 5139–$.80)

Cross-Grain Cutting With Segmented Helical Cutters Produces Good Surfaces and Flakes, H. A. Stewart and W. F. Lehmann, 9:104 (No. 5077–$.60)

Face Milling Can be Improved for Surfacing and Flaking, H. A. Stewart, 2:58 (No. 5140–$.40)

How to Cut Tree Disks Without Formation of Checks, H. Kubler and T-H. Chen, 7:57 (No. 5180–$.60)

Log and Sawmill Simulation Through Computer Graphics, S. M. Pnevmaticos, P. E. Dress, and F. R. Stocker, 3:53 (No. 5119–$.60)

Machinability Defects in Laminates Caused by Tool Wear, G. E. Power and D. Wulfekotter, 1:40 (No. 5085–$1.40)

Noise Levels in Softwood Lumber Mills, W. A. Dost, 8:25 (No. TN-272–$.60)

Sawmill Noise at the Operating Level, W. A. Dost, 8:13 (No. 5216–$1.00)

Steam-Injection Knife Improves Veneer Quality, D. C. Walser, 9:70 (No. 5222–$1.50)

Finishing & Overlaying

Bleaching of Mineral-Stained Maple, N. Levitin, 8:28 (No. 5171–$1.00)

Machinability Defects in Laminates Caused by Tool Wear, G. E. Power and D. Wulfekotter, 1:40 (No. 5085–$1.40)

One-Step Method of Making Veneer Polymer Composite Overlaid Plywood by Gamma Radiation, L. Paszner, T. Kaneko, H. T. Cho, and M. M. Micko, 10:39 (No. 5179–$1.40)

Pollution Abatement & Control

Noise Levels in Softwood Lumber Mills, W. A. Dost, 8:25 (No. TN-272–$.60)

Sawmill Noise at the Operating Level, W. A. Dost, 8:13 (No. 5216–$1.00)

Visual Method for Measuring Formaldehyde Release from Resin-Bonded Boards, J. M. Harkin, J. R. Obst, and W. F. Lehmann, 1:27 (No. 5110–$.80)

FUNDAMENTAL DISCIPLINES DIVISION

Biology

Ammoniacal Zinc Oxide Treatment as an Inhibitor of Fungi in Pine Lumber, J. K. Shields, R. L. Desai, and M. R. Clarke, 2:54 (No. 5133–$.80)

Bark Properties of Eight Western Softwoods, D. L. Cassens, 4:40 (No. 5073–$1.00)

Biodeterioration of Particleboard, E. R. Toole and H. M. Barnes, 10:55 (No. 5254–$.60)

Permeability of White Spruce Wet Stored in Labrador, H. H. Unligil and J. Krzyzewski, 12:33 (No. 5280–$1.00)

Seedling Characteristics and Kraft Pulping Properties of Young Douglas-Fir, W. J. Bublitz and S. N. Chia, 3:48 (No. 5135–$1.00)

Survival and Feeding of Subterranean Termites on Tropical Woods, R. H. Beal, F. L. Carter, and C. R. Southwell, 8:44 (No. 5210–$1.00)

Chemistry

Investigation of the Chemically Reactive Constituents of Atmospheric Emissions From Hogged-Fuel-Fired Boilers in Oregon, D. C. Junge and K. T. Kwan, 10:25 (No. 5232–$1.00)

Softening Temperature, Ash Content, and Bond Quality of Polyvinyl-Acetate-Emulsion Adhesives, E. G. Bergin and S. Chow, 11:45 (No. 5231–$1.00)

Uptake by Grape Plants of Preservatives From Pressure-Treated Posts Not Detected, M. P. Levi, D. Huisingh, and W. B. Nesbitt, 9:97 (No. 5208–$.40)

Versatile Fire Retardants from Amino Resins, S. C. Juneja and L. R. Richardson, 5:19 (No. 5094–$1.00)

Physics

Bark Properties of Eight Western Softwoods, D. L. Cassens, 4:40 (No. 5073–$1.00)

Determination of Small Linear Expansion Coefficients from Curvature of Two-Ply Laminate Strips, O. Suchsland, 4:38 (No. 5101–$.40)

Estimating Preservative Treatability of Wood From its Air-Flow Properties, P. A. Cooper, G. Bramhall, and N. A. Ross, 9:99 (No. 5200–$1.00)

Freezing and Thawing Times for Black Walnut, G. A. Cooper and S. H. Barham, 6:54 (No. 5170–$.60)

Gross Heat of Combustion of Five Hardwood Species at Differing Moisture Contents, W. K. Murphey and B. E. Cutter, 2:44 (TN-253–$.40)

How to Cut Tree Disks Without Formation of Checks, H. Kubler and T-H. Chen, 7:57 (No. 5180–$.60)

Improved Resistance Moisture Measurement Techniques: Pulsed Current Meter and Wood Element Sensors, R. F. Couture and J. L. Hill, 4:17 (No. 5123–$1.40)

Improving the Properties of Commercial Phenolic-Bonded, Structural-Type Particleboards by Oil Tempering, H. Hall and R. O. Gertjejansen, 3:40 (No. 5109–$.60)

Longitudinal Shrinkage of Western Redcedar, Western Hemlock and True Fir, L. D. Espenas, 10:46 (TN-281–$.60)

One-Step Method of Making Veneer Polymer Composite Overlaid Plywood by Gamma Radiation, L. Paszner, T. Kaneko, H. T. Cho, and M. M. Micko, 10:39 (No. 5179–$1.40)

Removal of Emulsified Oil by Sorption on Southern Pine Bark, W. G. Glasser and F. S. Lin, 9:87 (No. 5215–$1.00)

Use of Bark to Remove Heavy Metal Ions from Waste Solutions, J. M. Randall, V. Garrett, R. L. Berman, and A. C. Waiss, Jr., 9:80 (No. 5199–$1.00)

Wood Engineering & Mechanical Properties

Bark Properties of Eight Western Softwoods, D. L. Cassens, 4:40 (No. 5073–$1.00)

Comparison of Mechanical Properties for Non-Load-Bearing Panels in Walls, E. L. Back, E. I. E. Didriksson, and K. G. Norberg, 10:48 (No. 5207–$1.40)

Description of a Laminated Oak Beam L. J. Nemeth, 12:27 (No. 4903–$1.20)

Determination of Elastic Parameters of Full Size Wood Composite Boards, T. E. McLain and J. Bodig, 4:48 (No. 5158–$1.50)

Effect of Prescribed Defects on Tensile Properties of Douglas-Fir Plywood Strips, W. M. McGowan, 5:39 (No. 5150–$1.20)

Effect of Size on Tensile Strength of Clear Douglas-Fir and Hem-Fir, R. H. Kunesh and J. W. Johnson, 8:32 (No. 5197–$1.00)

Effect of Temperature, Time, and Drying Medium on the Strength and Gluability of Douglas-Fir and Southern Pine Veneer, C. J. Kozlik, 2:46 (No. 5027–$1.50)

Effects of Equilibrium Moisture Content Changes on Hardboard Properties, J. D. McNatt, 2:29 (No. 5087–$1.40)

Evaluation of Models for Predicting Tensile Strength of 2- by 4-Inch Lumber, C. C. Gerhards and R. L. Ethington, 12:46 (No. 5247–$1.50)

Evaluation of Some Tropical Woods Imported into the United States from South America, R. C. Gilmore and A. C. Barefoot, 2:24 (No. 5118–$1.00)

Gusset Plates from Plywood and Hardboard Scrap, D. H. Percival, S. K. Suddarth, and Q. B. Comus, 3:43 (TN-268–$.40)

Impact Behavior of Particleboard as Related to Some Other Physical Properties, A. Johnson and J. G. Haygreen, 11:22 (No. 5245–$1.20)

Improving the Properties of Commercial Phenolic-Bonded, Structural-Type Particleboards by Oil Tempering, H. Hall and R. O. Gertjejansen, 3:40 (No. 5109–$.60)

Influence of Fiber Alignment on Stiffness and Dimensional Stability of High-Density Dry-Formed Hardboard, P. E. Steinmetz and C. W. Polley, 5:45 (No. 5160–$1.00)

New Torsion Test for Particleboard, P. Gaudert, 2:35 (TN-258–$.60)

Potassium Fertilization Effects on the Static Bending Properties of Red Pine Wood, R. L. Gray and G. H. Kyanka, 9:92 (No. 5152–$1.00)

Prediction of Elastic Constants of Particleboard, M. O. Hunt and S. K. Suddarth, 5:52 (No. 5191–$1.20)

Properties of Structural Particleboards, W. F. Lehmann, 1:19 (No. 5070–$1.40)

Properties of Structural Particleboards from Douglas-Fir Forest Residues, W. F. Lehmann and R. L. Geimer, 10:17 (No. 5242–$1.50)

Proposed Strength Formulas for Wood Box Columns, L. W. Neubauer and V. K. Arora, 1:31 (No. 5075–$1.00)

Residual Strength of Fire-Damaged Laminated Beams, S. P. Fox, 1:48 (TN-255–$.60)

Shear Strength of Wood Beams, F. J. Keenan, 9:63 (No. 5144–$1.50)

Strength Characteristics of Two-Ply Vertically Laminated Beams of Southern Pine, R. H. McAlister, 8:39 (No. 5214–$1.00)

Strength and Stiffness of Roof Diaphragms With Different Percentages of the Decking Edge Glued, J. W. Johnson, 4:36 (TN-264–$.60)

Tensile Strength of Douglas-Fir Laminated-Veneer Lumber, J. C. Bohlen, 1:54 (No. 5111–$1.00)

Timber Structures Reinforced With Light Gage Steel, G. E. Coleman and H. T. Hurst, 7:45 (No. 4934–$1.80)

Three Tests on Nailhead Performance in Wood-Base Panels, P. Chow, 11:41 (TN-278–$.80)

FPRS Author Index . . . Vol. 24, 1974

A

Adair, K. T., Developments and Progress in Research Management, 4:11 (No. 5193–$.60)

Amburgey, T. L., Organisms Causing Discoloration and Deterioration of Asphalt Shingles, 6:52 (No. 5149–$.60)

Andersen, A. G., *see* Kreibich, R. E.

Anderson, A. B., A. Wong, and K-T. Wu, Utilization of White Fir Bark and Its Extract in Particleboard, 1:51 (No. 5010–$.80)

Anderson, A. B., A. Wong, and K-T. Wu, Utilization of White Fir Bark and Its Extract in Particleboard, 7:40 (No. 5164–$1.20)

Anderson, A. B., K-T. Wu, and A. Wong, Utilization of Ponderosa Pine Bark and Its Extract in Particleboard, 8:48 (No. 5217–$1.20)

Anderson, W. C., An Economist's View of the Pine-Site Hardwood Problem, 4:14 (No. 5211–$.60)

Arora, V. K., *see* Neubauer, L. W.

Atherton, G. H., *see* Laity, W. W.

B

Babcock, H. M., Deciding on Priority Projects, 9:52 (No. 5302–$.60)

Back, E. L., E. I. E. Didriksson, and K. G. Norberg, Comparison of Mechanical Properties for Non-Load-Bearing Panels in Walls, 10:48 (No. 5207–$1.40)

Back, E. L., *see* Didriksson, E. I. E.

Baltes, R. C., *see* Wengert, E. M.

Barefoot, A. C., *see* Gilmore, R. C.

Barham, S. H., *see* Cooper, G. A.

Barnes, H. M., *see* Toole, E. R.

Beal, R. H., F. L. Carter, and C. R. Southwell, Survival and Feeding of Subterranean Termites on Tropical Woods, 8:44 (No. 5210–$1.00)

Bergin, E. G., and S. Chow, Softening Temperature, Ash Content and Bond Quality of Polyvinyl-Acetate-Emulsion Adhesives, 11:45 (No. 5231–$1.00)

Berman, R. L., *see* Randall, J. M.

Biltonen, F. E., J. R. Erickson, and J. A. Mattson, Preliminary Economic Analysis of Whole-Tree Chipping and Bark Removal, 3:45 (No. 5132–$.60)

Bodig, J., *see* McLain, T. E.

Bohlen, J. C., Tensile Strength of Douglas-Fir Laminated-Veneer Lumber, 1:54 (No. 5111–$1.00)

Boone, R. S., *see* McMillen, J. M.

Boone, R. S., *see* Vital, B. E.

Bramhall, G., *see* Cooper, P. A.

Bublitz, W. J., and S. N. Chia, Seedling Characteristics and Kraft Pulping Properties of Young Douglas-Fir, 3:48 (No. 5135–$1.00)

Butcher, J. A., and J. Drysdale, Field Trials With Captafol–an Acceptable Antisapstain Chemical, 11:28 (No. 5267–$.60)

C

Carroll, M. N., A New Approach to Quality Control in the Manufacture of Exterior Softwood Plywood, 4:24 (No. 5104–$1.40)

Carter, F. L., *see* Beal, R. H.

Cassens, D. L., Bark Properties of Eight Western Softwoods, 4:40 (No. 5073–$1.00)

Cech, M. Y., F. Pfaff, and D. R. Huffman, CCA Retention and Disproportioning in White Spruce, 7:26 (No. 5185–$1.40)

Chen, C. M., *see* Rice, J. T.

Chen, T-H., *see* Kubler, H.

Chia, S. N., *see* Bublitz, W. J.

Cho, H. T., *see* Paszner, L.

Chow, P., Three Tests on Nailhead Performance in Wood-Base Panels, 11:41 (TN 278–$.80)

Chow, S., and P. R. Steiner, Resistance to Cyclic Exposure at Extreme Low Temperature of Urea Resin Bonds, 5:35 (No. 5157–$.80)

Chow, S., *see* Bergin, E. G.

Christensen, R. L. and P. Robitschek, Efficiency of Resin-Wood Particle Blending, 7:22 (No. 5196–$1.20)

Christopher, J. F., Present and Prospective Hardwood Utilization in the South, 10:13 (No. 5252–$.60)

Clark, A. III, and M. A. Taras, Effect of Harvesting to Various Merchantable Limits on Loblolly Pine Logging Residue, 6:45 (No. 5195–$.80)

Clarke, M. R., *see* Shields, J. K.

Coleman, G. E., and H. T. Hurst, Timber Structures Reinforced With Light Gage Steel, 7:45 (No. 4934–$1.80)

Comus, Q. B., *see* Percival, D. H.

Cooper, G. A., and S. H. Barham, Freezing and Thawing Times for Black Walnut, 6:54 (No. 5170–$.60)

Cooper, P. A., G. Bramhall, and N. A. Ross, Estimating Preservative Treatability of Wood From its Air-Flow Properties, 9:99 (No. 5200–$1.00)

Couture, R. F., and J. L. Hill, Improved Resistance Moisture Measurement Techniques: Pulsed Current Meter and Wood Element Sensors, 4:17 (No. 5123–$1.40)

Cox, L. A., Transfer of Science and Technology in Successful Innovation, 9:44 (No. 5294–$1.00)

Cutter, B. E., *see* Murphey, W. K.

D

Desai, R. L., *see* Shields, J. K.

Dickson, J., Use of the Semantic Differential in Developing Forest Products Marketing Strategies, 6:12 (No. 5136–$.40)

Didriksson, E. I. E., *see* Back, E. L.

Didriksson, E. I. E., J. O. Nyren, and E. L. Back, The Splitting of Wood-Base Building Boards Due to Edge Screwing, 7:35 (No. 5186–$1.00)

Dirr, M. A., *see* Still, S. M.

Dost, W. A., Noise Levels in Softwood Lumber Mills, 8:25 (No. TN-272–$.60)

Dost, W. A., Sawmill Noise at the Operating Level, 8:13 (No. 5216–$1.00)

Dress, P. E., *see* Pnevmaticos, S. M.

Drysdale, J., *see* Butcher, J. A.

Duncan, T. F., Normal Resin Distribution in Particleboard Manufacture, 6:36 (No. 5080–$1.50)

E

Erickson, J. R., *see* Biltonen, F. E.

Espenas, L. D., Longitudinal Shrinkage of Western Redcedar, Western Hemlock, and True Fir, 10:46 (TN-281–$.60)

Ethington, R. L., *see* Gerhards, C. C.

F

Fasick, C. A., G. L. Tyre, and F. M. Riley, Jr., Weight-Scaling Tree-Length Timber for Veneer Logs, Saw Logs, and Pulpwood, 6:17 (No. 5188–$.80)

Flann, I. B., *see* Pnevmaticos, S. M.

Fleischer, H. O., Response of a Public Research Laboratory to Changing Needs, 9:49 (No. 5305–$.60)

Fox, S. P., Residual Strength of Fire-Damaged Laminated Beams, 1:48 (TN-255–$.60)

G

Garrett, V., *see* Randall, J. M.

Gartner, J. B., *see* Still, S. M.
Gaudert, P., New Torsion Test for Particleboard, 2:35 (TN-258–$.60)
Geimer, R. L., *see* Lehmann, W. F.
Gerhards, C. C., and R. L. Ethington, Evaluation of Models for Predicting Tensile Strength of 2- by 4-Inch Lumber, 12:46 (No. 5247–$1.50)
Gertjejansen, R. O., *see* Hall, H.
Gilmore, R. C., and A. C. Barefoot, Evaluation of Some Tropical Woods Imported into the United States from South America, 2:24 (No. 5118–$1.00)
Glasser, W. G. and F. S. Lin, Removal of Emulsified Oil by Sorption on Southern Pine Bark, 9:87 (No. 5215–$1.00)
Gray, R. L., and G. H. Kyanka, Potassium Fertilization Effects on the Static Bending Properties of Red Pine Wood, 9:92 (No. 5152–$1.00)
Gregory, A. S., Strategic Planning of Research and Development at Weyerhaeuser, 9:37 (No. 5292–$1.40)

H

Habermann, H., *see* Lutz, J. F.
Hall, H., and R. O. Gertjejansen, Improving the Properties of Commercial Phenolic-Bonded, Structural-Type Particleboards by Oil Tempering, 3:40 (No. 5109–$.60)
Harkin, J. M., J. R. Obst, and W. F. Lehmann, Visual Method for Measuring Formaldehyde Release from Resin-Bonded Boards, 1:27 (No. 5110–$.80)
Haygreen, J. G., *see* Johnson, A.
Hill, J. L., *see* Couture, R. F.
Host, J., Lumber Production: Analyzing Costs, Sales, and Supply Relationships, 11:49 (No. 5234–$1.20)
Howard, E. T., Needleboards–an Exploratory Study, 5:50 (TN-265–$.40)
Howard, E. T., Slash Pine Rootwood in Flakeboard, 6:29 (No. 5167–$1.50)
Huffman, D. R., *see* Cech, M. Y.
Huisingh, D., *see* Levi, M. P.
Hunt, M. O., and S. K. Suddarth, Prediction of Elastic Constants of Particleboard, 5:52 (No. 5191–$1.20)
Hurst, H. T., *see* Coleman, G. E.

I

Irland, L. C., Forest Products and the National Housing Goals, 2:12 (No. 5148–$1.20)
Irland, L. C., Futures Markets: an Annotated Bibliography 7:12 (No. TN-276–$.20)

J

Johnson, A., and J. G. Haygreen, Impact Behavior of Particleboard as Related to Some Other Physical Properties, 11:22 (No. 5245–$1.20)
Johnson, J. W., Strength and Stiffness of Roof Diaphragms with Different Percentages of the Decking Edge Glued, 4:36 (TN-264–$.60)
Johnson, J. W., *see* Kunesh, R. H.
Johnson, W. W., and R. O. McMahon, Future Outlook for Oregon's Particleboard Industry, 1:13 (No. 5137–$.60)
Juneja, S. C., *see* King, F. W.
Juneja, S. C., and L. R. Richardson, Versatile Fire Retardants from Amino Resins, 5:19 (No. 5094–$1.00)
Junge, D. C., and K-T. Kwan, An Investigation of the Chemically Reactive Constituents of Atmospheric Emissions from Hogged-Fuel-Fired Boilers in Oregon, 10:25 (No. 5232–$1.00)

K

Kaneko, T., *see* Paszner, L.
Keays, J. L., Full-Tree and Complete-Tree Utilization for Pulp and Paper, 11:13 (No. 5277–$.80)
Keenan, F. J., Shear Strength of Wood Beams, 9:63 (No. 5144–$1.50)
King, F. W., and S. C. Juneja, New Fire-Retardant Treatment for Western Redcedar Shingles, 2:18 (No. 5025–$1.20)
Kingsley, M. C. S., *see* Robichaud, Y.
Knight, H. A., *see* Murphy, P. A.
Koch, P., Serrated Kiln Sticks and Top Load Substantially Reduce Warp in Southern Pine Studs Dried at 240°F, 11:30 (No. 5256–$1.00)
Koch, P., Time to Dry 2-, 3-, and 4-Inch S4S Southern Pine at 240°F, as Related to Board Width, 3:35 (No. 5067–$1.00)
Koch, P., Trials of Prototype Roll-Feed, High Temperature Dryer for 8/4 Southern Pine, 5:24 (No. 5175–$1.00)
Kozlik, C. J., Effect of Temperature, Time, and Drying Medium on the Strength and Gluability of Douglas-fir and Southern Pine Veneer, 2:46 (No. 5027–$1.50)
Krahmer, R. L., *see* Miller, D. J.
Kreibich, R. E., and A. G. Andersen, Measuring Durability of Adhesive Resins on Paper Substrates, 1:36 (No. 5031–$.80)
Krzyzewski, J., *see* Unligil, H. H.
Kubler, H., Drying Tree Disks Simply and Without Defects, 7:33 (No. 5042–$.60)
Kubler, H. and T-H. Chen, How To Cut Tree Disks Without Formation of Checks, 7:57 (No. 5180–$.60)
Kunesh, R. H. and J. W. Johnson, Effect of Size on Tensile Strength of Clear Douglas-fir and Hem-fir, 8:32 (No. 5197–$1.00)
Kwan, K. T., *see* Junge, D. C.
Kyanka, G. H., *see* Gray, R. L.

L

Laity, W. W., G. H. Atherton, and J. R. Welty, Comparisons of Air and Steam as Veneer Drying Media, 6:21 (No. 5030–$1.50)
Lehmann, W. F., Properties of Structural Particleboards, 1:19 (No. 5070–$1.40)
Lehmann, W. F., and R. L. Geimer, Properties of Structural Particleboards from Douglas-fir Forest Residues, 10:17 (No. 5242–$.50)
Lehmann, W. F., *see* Harkin, J. M.
Lehmann, W. F., *see* Stewart, H. A.
Lehmann, W. F., *see* Vital, B. E.
Levi, M. P., D. Huisingh, and W. B. Nesbitt, Uptake by Grape Plants of Preservatives From Pressure-Treated Posts Not Detected, 9:97 (No. 5208–$.40)
Levitin, N., Bleaching of Mineral-Stained Maple, 8:28 (No. 5171–$1.00)
Lin, F. S., *see* Glasser, W. G.
Lutz, J. F., H. Habermann, and H. R. Panzer, Press-Drying Green, Flat-sliced Walnut Veneer to Reduce Buckling and End Waviness, 5:29 (No. 5165–$1.20)

M

Mackay, J. F. G., High Temperature Kiln-Drying of Northern Aspen 2- by 4-Inch Light-Framing Lumber, 10:32 (No. 5237–$.80)
Marra, G. G., The Dilemma in Academic Research, 9:58 (No. 5293–$.80)
Mattson, J. A., *see* Biltonen, F. E.
McAlister, R. H., Edge-Glued Lumber from Low-Grade Southern Pine, 7:17 (No. 5178–$1.20)
McAlister, R. H., Strength Characteristics of Two-Ply Vertically Laminated Beams of Southern Pine, 8:39 (No. 5214–$1.00)
McEwan, T. K., Analysis of the Effect of the Lumber Recovery Factor (LRF) on Sawmill Costs, 3:17 (No. 5103–$.60)
McGowan, W. M., Effect of Prescribed Defects on Tensile Properties of Douglas-Fir Plywood Strips, 5:39 (No. 5150–$1.20)
McLain, T. E., and J. Bodig, Determination of Elastic Parameters of Full-Size Wood Composite Boards, 4:48 (No. 5158–$1.50)
McMahon, R. O., *see* Johnson, W. W.
McMillen, J. M., and R. S. Boone, Kiln-Drying Selected Colombian Woods, 4:31 (No. 5147–$1.20)
McNatt, J. D., Effects of Equilibrium Moisture Content Changes on Hardboard Properties, 2:29 (No. 5087–$1.40)
Micko, M. M., *see* Paszner, L.
Miller, D. J., J. D. Wellons, R. L. Krahmer, and P. H. Short, Reinforcing Plastics with Douglas-Fir Bark Fiber, 8:18 (No. 5205–$1.20)
Murphey, W. K., and B. E. Cutter, Gross Heat of Combustion of Five Hardwood Species at Differing Moisture Contents, 2:44 (TN-253–$.40)
Murphy, P. A., and H. A. Knight, Hardwood Resources on Southern Pine Sites, 7:13 (No. 5238–$.80)

N

Nemeth, L. J., Description of a Laminated Oak Beam Design and Test, 12:27 (No. 4903–$1.20)
Neubauer, L. W., and V. K. Arora, Proposed Strength Formulas for

Wood Box Columns, 1:31 (No. 5075–$1.00)
Nesbitt, W. B., *see* Levi, M. P.
Norberg, K. G., *see* Back, E. L.
Nyren, J. O., *see* Didriksson, E. I. E.

O

Obst, J. R., *see* Harkin, J. M.

P

Panzer, H. R., *see* Lutz, J. F.
Paszner, L., T. Kaneko, H. T. Cho, and M. M. Micko, One-Step Method of Making Veneer Polymer Composite Overlaid Plywood by Gamma Radiation, 10:39 (No. 5179–$1.40)
Percival, D. H., S. K. Suddarth, and Q. B. Comus, Gusset Plates from Plywood and Hardboard Scrap, 3:43 (TN-268–$.40)
Petro, F. J., *see* Robichaud, Y.
Pfaff, F., *see* Cech, M. Y.
Pleasonton, A., Trends in Forest Land Values, 1:16 (No. 5072–$.60)
Pnevmaticos, S. M., P. E. Dress, and F. R. Stocker, Log and Sawmill Simulation Through Computer Graphics, 3:53 (No. 5119–$.60)
Pnevmaticos, S. M., and I. B. Flann, Logs vs. Bolts: Effect of Length on Dimension Stock Yields, 6:49 (No. 5050–$.60)
Polley, C. W., *see* Steinmetz, P. E.
Power, G. E., and D. Wulfekotter, Machinability Defects in Laminates Caused by Tool Wear, 1:40 (No. 5085–$1.40)

R

Randall, J. M., V. Garrett, R. L. Berman, and A. C. Waiss, Jr., Use of Bark to Remove Heavy Metal Ions from Waste Solutions, 9:80 (No. 5199–$1.00)
Rice, J. T., and C. M. Chen, Study of Dryout Resistance of Phenolic Copolymer Resins for Pine Plywood Glues – Part I, 3:20 (No. 5125–$1.40)
Richardson, L. R., *see* Juneja, S. C.
Riley, F. M., *see* Fasick, C. A.
Robertson, J. E., Evaluation of Asian Plywood Glue Extenders Based on Personal Plant-site Observations in 1973, 11:35 (No. 5228–$1.40)
Robichaud, Y., F. J. Petro, and M. C. S. Kingsley, Aspen Lumber and Dimension Stock Recovery in Relation to Sawing Pattern, 3:26 (No. 5126–$1.00)
Robitschek, P., *see* Christensen, R. L.
Ross, N. A., *see* Cooper, P. A.

S

Sawyer, E. W., Jr., *see* Strickler, M. D.
Shields, J. K., R. L. Desai, and M. R. Clarke, Ammoniacal Zinc Oxide Treatment as an Inhibitor of Fungi in Pine Lumber, 2:54 (No. 5133–$.80)
Shen, K. C., Improving the Surface Quality of Particleboard by High-Temperature Pressing, 10:36 (No. 5206–$.80)
Shen, K. C., Modified Powdered Spent Sulfite Liquor as Binder for Exterior Waferboard, 2:38 (No. 5093–$1.40)
Short, P. H., *see* Miller, D. J.
Southwell, C. R., *see* Beal, R. H.
Space, J. C., Predicting Product Recovery in Southern Pine Using Dendrometry and STX, 9:85 (No. 5198–$.60)
Steiner, P. R., *see* Chow, S.
Steinhagen, H-P., Effect of Kiln Air Velocity, at Various Moisture Content Levels, on Drying Rate of 4/4 Yellow-Poplar Sapwood, 4:45 (No. 4943–$.60)
Steinmetz, P. E., and C. W. Polley, Influence of Fiber Alignment on Stiffness and Dimensional Stability of High-Density Dry-Formed Hardboard, 5:45 (No. 5160–$1.00)
Stern, E. G., Hardened-Steel Versus Stiff-Stock Nails in Warehouse Pallets, 11:55 (TN 277–$.60)
Sternitzke, H. S., Eastern Hardwood Resources: Trends and Prospects, 3:13 (No. 5183–$.80)
Stevens, R. R., Apparatus to Facilitate Comparison of Abrasiveness of Wood Composition Panel Products, 8:37 (No. TN-269–$.60)
Stewart, H. A., Comparison of Factors Affecting Power for Abrasive and Knife Planing of Hardwoods, 3:31 (No. 5139–$.80)
Stewart, H. A., Face Milling Can be Improved for Surfacing and Flaking, 2:58 (No. 5140–$.40)
Stewart, H. A. and W. F. Lehmann, Cross-Grain Cutting With Segmented Helical Cutters Produces Good Surfaces and Flakes, 9:104 (No. 5077–$.60)
Still, S. M., M. A. Dirr, and J. B. Gartner, Effect of Nitrogen and Composting on Decomposition of Barks from Four Hardwood Species, 7:54 (No. 5194–$.60)
Stocker, F. R., *see* Pnevmaticos, S. M.
Strickler, M. D., and E. W. Sawyer, Jr., Attapulgite Clay, a Filler and Exterior Plywood Adhesive, 11:17 (No. 5239–$1.20)
Suchsland, O., Determination of Small Linear Expansion Coefficients from Curvature of Two-Ply Laminate Strips, 4:38 (No. 5101–$.40)
Suddarth, S. K., *see* Hunt, M. O.
Suddarth, S. K., *see* Percival, D. H.

T

Taras, M. A., *see* Clark, A. III
Thompson, R. D., Marketability of Aspen Studs, 12:23 (No. 5265–$1.00)
Toole, E. R., and H. M. Barnes, Biodeterioration of Particleboard, 10:55 (No. 5254–$.60)
Tyre, G. L., *see* Fasick, C. A.

U

Unligil, H. H., and J. Krzyzewski, Permeability of White Spruce Wet Stored in Labrador, 12:33 (No. 5280–$1.00)

V

Vick, C. B., *see* Zornig, H. F.
Vital, B. R., W. F. Lehmann, R. S. Boone, Effects of Species and Panel Densities on Properties of Exotic Hardwood Particleboard, 12:37 (No. 5291–$1.50)

W

Waiss, A. C., *see* Randall, J. M.
Walser, D. C., Steam-Injection Knife Improves Veneer Quality, 9:70 (No. 5222–$1.50)
Welch, R. L., Logging Residues in Florida, Georgia, and South Carolina, 10:30 (No. 5235–$.60)
Wellons, J. D., *see* Miller, D. J.
Welty, J. R., *see* Laity, W. W.
Wengert, E. M., Maximum Initial Moisture Content for Kiln-Drying 4/4 Hardwoods at High Temperatures. 8:54 (No. 5221–$.60)
Wengert, E. M., and R. C. Baltes, A "Pinned" Sticker to Reduce Crook in Kiln-Drying Lumber, 8:23 (No. TN-275–$.40)
Wong, A., *see* Anderson, A. B.
Wu, K. T., *see* Anderson, A. B.
Wulfekotter, D., *see* Power, G. E.
Wylie, A. E., Cooperative Research Planning, 9:55 (No. 5295–$.60)

Y

Young, H. E., Complete-Tree Concept: 1964-1974. 12:13 (No. 5269–$.80)

Z

Zornig, H. F., and C. B. Vick, Methods of Nailing and Adhesive Rheology Affect the Strength of Nailed-Glued Construction Joints. 12:17 (No. 5266–$1.20)

Due to space limitations, the FPRS membership drive update does not appear in this issue. Members joining in October and November will be listed in the January issue.